



Weldpoly1200 LF

Weldpoly1200/48 hydraulically operated butt-welding machine, suitable for PE and PP pipes and fittings from 630 to 1200mm OD, alternatively 24 to 48". Available to weld according to ISO/DVS/POP003 SLP & DLP low pressure. The use of virgin Aluminium castings and German hydraulic seals allows for lower weight without compromising strength and performance. Welding can be carried out between clamps 3 & 4 for tees, bends and manifold work. Can be integrated with optional data logger and overhead electric crane.



TECHNICAL SPECIFICATIONS

Welding range 630 to 1200mm: to SDR 11 (PN16). 630 to 800mm: to SDR 9

Welding force maximum 1200mm OD SDR 11, according to DVS 2207-1, ISO 21307 and POP003 low-pressure specifications.

Main frame includes 4 light weight alloy main clamps of 1200mm diameter.

Layer clamps: 1200x1100, 1100x1000, 1000x900, 900x800, 800x710, 710x630.

Machine can be supplied with any combination of liner diameters.

Aluminium PTFE coated heating plate with electronic temperature control. Heating plate automatically releases from pipe ends after heating.

Electrically operated facing tool for correct preparation of pipe ends.

Stand for heating plate and facing tool.

Electrohydraulic pump with controls, accumulator and quick release hoses. Includes countdown timers for heating and cooling phases.

Genuine 2 year international warranty.

Optional 1,000kg crane assembly, wheeled trolley and aluminium or steel stub end device for welding end fittings.

Wired ready to accept Weldpoly or other data logger.

Tool box including tools, bolts etc.

400 volt 50/60 Hz 3 phase (29 kw, 47.3 A). 480 volt 3 phase 60 Hz also available

Minimum generator required: 400 volt 50 hz 3 phase, 32 KVA. Provide full machine details to generator supplier before purchase.

Weight 4,522kg (including crane and stub device)

Total cylinder area: 50.6cm², maximum pump pressure 180 bar

Please note technical specifications of Weldpoly machines may change without notice